9001K1L35LYYH5

Harmony 9001K, illuminated push-button, metal, plastic guard flush, yellow, 30mm, spring return, LED yellow, 24-28V, 1 NO





Main

Man	
Range of Product	Harmony 9001K
Product or Component Type	Illuminated push-button
Device short name	К
Type of operator	Spring return
Operator profile	Yellow flush
Operator additional information	Plastic guard

Complementary

Bezel material	Metal	
Mounting diameter	1.18 in (30 mm)	
Light source	LED	
Light source	LED	
Bulb base	BA 9s	
Light block supply	Direct	
[Us] rated supply voltage	2428 V AC/DC	
Contacts type and composition	1 NO	
Connections - terminals	Screw clamp terminals	
Operating position	Any position	
[le] rated operational current	10 A, AC-15 10 A, DC-13	
Contact operation	Standard	
Device presentation	Complete product	

Environment

Product Certifications	UL listed file E42259 CCN NKCR CE CSA LR 25490 class 3211 03 NEMA
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	785901753469	
Nbr. of units in pkg.	1	
Package weight(Lbs)	8.00 oz (226.796 g)	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.08 in (12.903 cm)
Package 1 width	2.00 in (5.08 cm)
Package 1 Length	12.90 in (32.774 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months