

Description

The DIODES™ AP7353 is a low dropout regulator with high output voltage accuracy, low $R_{DS(ON)}$, high PSRR, low output noise, and low quiescent current. This regulator is based on a CMOS process.

The AP7353 includes a voltage reference, error amplifier, current-limit circuit, and an enable input to turn it on and off. With the integrated resistor network, fixed output voltage versions can be delivered.



With its high PSRR, good line regulation, and fast load transient response, the AP7353 is well suited for handheld/wearable communication equipment that require stable voltage sources.

The AP7353 is packaged in the X1-WLB0707-4 (Type A1) and X2-DFN1010-4 (Type B), which allow for a reduced footprint and denser PCB layout.

Features

- Low V_{IN} and Wide V_{IN} Range: 2.0V to 5.5V
- Guarantee Output Current, 250mA
- V_{OUT} Accuracy $\pm 1\%$
- Ripple Rejection 90dB at 1kHz, $I_{OUT} = 10mA$
- Ripple Rejection 70dB at 10kHz, $I_{OUT} = 250mA$
- Low Output Noise, 10 μ Vrms from 10Hz to 100kHz at 10mA
- Quiescent Current as Low as 18 μ A (Typ.)
- V_{OUT} Fixed 1.8V to 4.7V
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free, Green Device (Note 3)**
- **For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please [contact us](mailto:contact@diodes.com) or your local Diodes representative. <https://www.diodes.com/quality/product-definitions/>**

Pin Assignments




Applications

- Smartphones/PADs
- RF supplies
- Cameras
- Portable videos
- Portable media players
- Wireless adaptors
- Wireless communication

Notes: 1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
 2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
 3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.


Typical Applications Circuit




Pin Descriptions

| Pin Name | Pin Number | | Function |
|-------------|---------------------------|--------------------------|---|
| | X1-WLB0707-4 (Type A1) | X2-DFN1010-4 (Type B) | |
| IN | 1 | 4 | Power Input Pin |
| EN | 2 | 3 | Enable Pin This pin should be driven either high or low and must not be floating. Driving this pin high enables the regulator, while pulling it low puts the regulator into shutdown mode |
| GND | 3 | 2 | Ground |
| OUT | 4 | 1 | Power Output Pin |
| Exposed Pad | — | EP | In PCB layout, prefer to use large copper area to cover this pad for better thermal dissipation, then connect this area to GND or leave it open. However, do not use it as GND electrode function alone |

Functional Block Diagram



AP7353 (Non-Discharge)



AP7353D (With Discharge)

Absolute Maximum Ratings (Note 4) (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

| Symbol | Parameter | Ratings | Unit |
|-----------|--------------------------------|--------------|------------------|
| ESD HBM | Human Body Mode ESD Protection | >2 | kV |
| ESD CDM | Charge Device Model | ± 500 | V |
| V_{IN} | Input Voltage | 6.0 | V |
| V_{EN} | Input Voltage EN | 6.0 | V |
| V_{OUT} | Output Voltage | -0.3 to 6.0 | V |
| I_{OUT} | Output Current | 250 | mA |
| P_D | Power Dissipation (Note 5) | X1-WLB0707-4 | 650 |
| | | X2-DFN1010-4 | 400 |
| T_A | Operating Ambient Temperature | -40 to +85 | $^\circ\text{C}$ |
| T_J | Operating Junction Temperature | +125 | $^\circ\text{C}$ |
| T_{STG} | Storage Temperature | -55 to +150 | $^\circ\text{C}$ |

- Notes:
- Stresses beyond those listed under *Absolute Maximum Ratings* can cause permanent damage to the device. These are stress ratings only and functional operation of the device at these conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods can affect device reliability.
 - Stresses beyond those listed under *Absolute Maximum Ratings* can cause permanent damage to the device. These are stress ratings only and functional operation of the device at these conditions is not implied. Exposure to absolute-maximum-rated conditions for extended period may affect device reliability. Ratings apply to ambient temperature at +25 $^\circ\text{C}$. The JEDEC High-K board design used to derive this data was a 2 inch \times 2 inch multilayer board with 1oz. internal power and ground planes and 2oz. copper traces on the top and bottom of the board

Recommended Operating Conditions (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)







| Symbol | Parameter | Min | Max | Unit |
|-----------|-------------------------------|-----|-----|------------------|
| V_{IN} | Input Voltage | 2.0 | 5.5 | V |
| I_{OUT} | Output Current | 0 | 250 | mA |
| T_A | Operating Ambient Temperature | -40 | +85 | $^\circ\text{C}$ |

Electrical Characteristics (@ $V_{EN} = V_{IN} = V_{OUT} + 1.0V$, or $V_{IN}=5.5V$ (for $V_{OUT}=4.7V$), $C_{IN} = C_{OUT} = 1\mu F$, $I_{OUT} = 1.0mA$ @ $T_A = +25^\circ C$, unless otherwise specified.)







| Parameter | Conditions | Min | Typ | Max | Unit | |
|---|---|-------------------|----------|------|-----------------|----|
| Input Voltage | $T_A = -40^\circ C$ to $+85^\circ C$ | 2.0 | — | 5.5 | V | |
| Output Voltage Accuracy (Note 11) | $V_{IN} = (V_{OUT_Nom} + 1.0V)$ to $5.5V$, $I_{OUT} = 1mA$ to $250mA$ | -1 | — | +1 | % | |
| Line Regulation ($dV_{OUT}/dV_{IN}/V_{OUT}$) | $V_{IN} = (V_{OUT_Nom} + 1.0V)$ to $5.5V$ | — | 0.02 | — | %/V | |
| Load Regulation ($dV_{OUT}/V_{OUT}/dI_{OUT}$) X1-WLB0707-4 (Type A1) | $V_{IN} = V_{OUT_Nom} + 1.0V$, or $V_{IN}=5.5V$ (for $V_{OUT}=4.7V$), $I_{OUT} = 1mA$ to $250mA$ | — | 0.001 | — | %/mA | |
| Load Regulation ($dV_{OUT}/V_{OUT}/dI_{OUT}$) X2-DFN1010-4 (Type B) | $V_{IN} = V_{OUT_Nom} + 1.0V$, $I_{OUT} = 1mA$ to $250mA$ | — | 0.004 | — | %/mA | |
| Quiescent Current (Note 7) | $I_{OUT} = 0mA$, $V_{EN} = 1.2V$ | — | 18 | 27 | μA | |
| Standby Current ($I_{STANDBY}$) | $V_{EN} = 0V$ (Disabled) | — | 0.1 | 1.0 | μA | |
| Output Current | — | — | — | 250 | mA | |
| Output Current Limit | $V_{OUT} = 90\% V_{OUT}$ | 260 | — | — | mA | |
| PSRR (Note 8) | $V_{IN} = [V_{OUT} + 1V]$, or $V_{IN}=5.5V$ (for $V_{OUT}=4.7V$) VDC + 0.2Vp-pAC, $V_{OUT} \geq 1.8V$, $I_{OUT} = 10mA$ | f = 100Hz | — | 90 | — | dB |
| | | f = 1kHz | — | 90 | — | |
| | | f = 10kHz | — | 70 | — | |
| Output Noise Voltage (Note 8) (Note 9) | BW = 10Hz to 100kHz, $I_{OUT} = 10mA$ | — | 10 | — | μV_{rms} | |
| Dropout Voltage (Note 6) X1-WLB0707-4 (Type A1) | $I_{OUT} = 250mA$ | $V_{OUT} = 1.8V$ | — | 115 | 237 | mV |
| | | $V_{OUT} = 2.5V$ | — | 75 | 166 | |
| | | $V_{OUT} = 2.8V$ | — | 73 | 152 | |
| | | $V_{OUT} = 2.85V$ | — | 73 | 152 | |
| | | $V_{OUT} = 2.9V$ | — | 71 | 150 | |
| | | $V_{OUT} = 3.0V$ | — | 68 | 147 | |
| | | $V_{OUT} = 3.1V$ | — | 68 | 147 | |
| | | $V_{OUT} = 3.2V$ | — | 67 | 142 | |
| | | $V_{OUT} = 3.3V$ | — | 65 | 138 | |
| | | $V_{OUT} = 3.6V$ | — | 60 | 119 | |
| Dropout Voltage (Note 6) X2-DFN1010-4 (Type B) | $I_{OUT} = 250mA$ | $V_{OUT} = 1.8V$ | — | 130 | 240 | mV |
| | | $V_{OUT} = 2.5V$ | — | 95 | 168 | |
| | | $V_{OUT} = 2.8V$ | — | 92 | 155 | |
| | | $V_{OUT} = 2.85V$ | — | 92 | 155 | |
| | | $V_{OUT} = 2.9V$ | — | 91 | 153 | |
| | | $V_{OUT} = 3.0V$ | — | 88 | 150 | |
| | | $V_{OUT} = 3.1V$ | — | 88 | 150 | |
| | | $V_{OUT} = 3.2V$ | — | 87 | 146 | |
| | | $V_{OUT} = 3.3V$ | — | 85 | 142 | |
| | | $V_{OUT} = 3.6V$ | — | 79 | 122 | |
| Output Voltage Temperature Coefficient | $I_{OUT} = 30mA$, $T_A = -40^\circ C$ to $+85^\circ C$ | — | ± 30 | — | ppm/ $^\circ C$ | |
| Turn-On Time | 90% of Typical V_{OUT} | — | 180 | — | μs | |
| EN Input Low Voltage | — | 0.0 | — | 0.4 | V | |
| EN Input High Voltage | — | 1.2 | — | 5.5 | V | |
| EN Input Leakage | $V_{EN} = 0$, $V_{IN} = 5.0V$ or $V_{EN} = 5.0V$, $V_{IN} = 0V$ | -1.0 | — | +1.0 | μA | |
| On Resistance of N-Channel for Auto-Discharge (Note 10) | $V_{IN} = V_{OUT_Nom} + 1.0V$, or $V_{IN}=5.5V$ (for $V_{OUT}=4.7V$), $V_{EN} = 0V$ (Disabled) | — | 35 | — | Ω | |
| Thermal Resistance Junction to Ambient (θ_{JA}) | X1-WLB0707-4 | — | 150 | — | $^\circ C/W$ | |
| | X2-DFN1010-4 (Type B) | — | 237 | — | | |

- Notes:
- Dropout voltage is the voltage difference between the input and the output at which the output voltage drops 2% below its nominal value.
 - Quiescent current is defined here as the difference in current between the input and the output.
 - This specification is guaranteed by design.
 - To make sure lowest environment noise minimizes the influence on noise measurement.
 - AP7353 has 2 options for output, built-in discharge and non-discharge.
 - Potential multiple grades based on following output voltage accuracy.







Typical Performance Characteristics








Typical Performance Characteristics (continued)



Typical Performance Characteristics (continued)




Typical Performance Characteristics (continued)




Typical Performance Characteristics (continued)

Enable Turn-On Response




Time (100µs/div)

Enable Turn-On Response




Time (100µs/div)

Line Transient Response




Time (40µs/div)

Line Transient Response




Time (40µs/div)

V_{IN} Slow Turn On



Time (4ms/div)


V_{IN} Slow Turn Off



Time (4ms/div)


Typical Performance Characteristics (continued)

Load Transient Response




Time (20µs/div)

Load Transient Response




Time (20µs/div)

Short Circuit and Thermal Shutdown



Time (20ms/div)

Enable Turn-Off



Time (400µs/div)

Application Information

Overview

The AP7353 is a 250mA low dropout regulator which provides low noise, high PSRR, and low quiescent current. With low quiescent current, this device is suitable for battery-powered applications, RF applications, and high-performance analog circuits.

Output Capacitor

An output capacitor (C_{OUT}) is needed to improve transient response and maintain stability. The AP7353 is stable with very small ceramic output capacitors. The recommended capacitor value is 1 μ F with low temperature influence properties, such as X7R or X5R. The minimum effective capacitance to maintain stable operation of the AP7353 is 0.7 μ F, which accounts for changes of temperature, DC bias, and manufacturing tolerances. The ESR (equivalent series resistance) of C_{OUT} should be lower than 2 Ω . If the application has large load variations, it is recommended to utilize low-ESR capacitors. It is recommended to place ceramic capacitors as close as possible to the OUT pin and the ground pin, and care should be taken to reduce the impedance in the layout.

Input Capacitor

To prevent the input voltage from dropping during load steps, it is recommended to utilize an input capacitor (C_{IN}). A minimum 1 μ F ceramic capacitor is recommended between IN and GND pins to decouple input power supply glitch. This input capacitor must be located as close as possible to the device to ensure input stability and reduce noise. For PCB layout, a wide copper trace is required for both IN and GND pins.

Enable Control

The AP7353 is turned on by setting the EN pin high, and is turned off by pulling it low. If this feature is not used, the EN pin should be tied to the IN pin to keep the regulator output on at all times. To ensure proper operation, the signal source used to drive the EN pin must be able to swing above and below the specified turn-on/off voltage thresholds listed in the *Electrical Characteristics* section.


Short-Circuit Protection

When the OUT pin is short-circuited to the GND, short-circuit protection will be triggered and clamp the output current to approximately 350mA. This feature protects the regulator from overcurrent and overheating damage.

Layout Considerations

For good ground loop and stability, the input and output capacitors should be located close to the IN, OUT, and GND pins of the device. The regulator GND pin should be connected to the external circuit ground to reduce voltage drop caused by trace impedance. Ground plane is generally used to reduce trace impedance. Wide trace should be used for large current paths from V_{IN} to V_{OUT} , and load circuit.

Ordering Information




| Part Number | Package Code | Package | 7" Tape and Reel | |
|------------------|--------------|------------------------|-------------------|--------------------|
| | | | Quantity | Part Number Suffix |
| AP7353-XXCV4-7 | CV4 | X1-WLB0707-4 (Type A1) | 3,000/Tape & Reel | -7 |
| AP7353-XXXCV4-7 | CV4 | X1-WLB0707-4 (Type A1) | 3,000/Tape & Reel | -7 |
| AP7353-XXFS4-7 | FS4 | X2-DFN1010-4 (Type B) | 5,000/Tape & Reel | -7 |
| AP7353-XXXFS4-7 | FS4 | X2-DFN1010-4 (Type B) | 5,000/Tape & Reel | -7 |
| AP7353D-XXCV4-7 | CV4 | X1-WLB0707-4 (Type A1) | 3,000/Tape & Reel | -7 |
| AP7353D-XXXCV4-7 | CV4 | X1-WLB0707-4 (Type A1) | 3,000/Tape & Reel | -7 |
| AP7353D-XXFS4-7 | FS4 | X2-DFN1010-4 (Type B) | 5,000/Tape & Reel | -7 |
| AP7353D-XXXFS4-7 | FS4 | X2-DFN1010-4 (Type B) | 5,000/Tape & Reel | -7 |

Marking Information

(1) X1-WLB0707-4 (Type A1)

(Top View)




\bar{X} : Identification Code
 Y : Year : 0~9
 W : Week : A~Z : 1~26 week;
 a~z : 27~52 week; z represents
 52 and 53 week

| Part Number | Package | Identification Code |
|------------------|------------------------|---------------------|
| AP7353-18CV4-7 | X1-WLB0707-4 (Type A1) | \bar{D} |
| AP7353-25CV4-7 | X1-WLB0707-4 (Type A1) | \bar{E} |
| AP7353-28CV4-7 | X1-WLB0707-4 (Type A1) | \bar{F} |
| AP7353-285CV4-7 | X1-WLB0707-4 (Type A1) | \bar{G} |
| AP7353-29CV4-7 | X1-WLB0707-4 (Type A1) | \bar{H} |
| AP7353-30CV4-7 | X1-WLB0707-4 (Type A1) | \bar{J} |
| AP7353-31CV4-7 | X1-WLB0707-4 (Type A1) | \bar{K} |
| AP7353-32CV4-7 | X1-WLB0707-4 (Type A1) | \bar{L} |
| AP7353-33CV4-7 | X1-WLB0707-4 (Type A1) | \bar{M} |
| AP7353-36CV4-7 | X1-WLB0707-4 (Type A1) | \bar{N} |
| AP7353-45CV4-7 | X1-WLB0707-4 (Type A1) | \bar{P} |
| AP7353D-18CV4-7 | X1-WLB0707-4 (Type A1) | \bar{R} |
| AP7353D-25CV4-7 | X1-WLB0707-4 (Type A1) | \bar{S} |
| AP7353D-28CV4-7 | X1-WLB0707-4 (Type A1) | \bar{T} |
| AP7353D-285CV4-7 | X1-WLB0707-4 (Type A1) | \bar{U} |
| AP7353D-29CV4-7 | X1-WLB0707-4 (Type A1) | \bar{V} |
| AP7353D-30CV4-7 | X1-WLB0707-4 (Type A1) | \bar{W} |
| AP7353D-31CV4-7 | X1-WLB0707-4 (Type A1) | \bar{X} |
| AP7353D-32CV4-7 | X1-WLB0707-4 (Type A1) | \bar{Y} |
| AP7353D-33CV4-7 | X1-WLB0707-4 (Type A1) | \bar{Z} |
| AP7353D-36CV4-7 | X1-WLB0707-4 (Type A1) | $\bar{2}$ |
| AP7353D-45CV4-7 | X1-WLB0707-4 (Type A1) | $\bar{3}$ |
| AP7353D-47CV4-7 | X1-WLB0707-4 (Type A1) | $\bar{4}$ |

Marking Information (continued)

(2) X2-DFN1010-4 (Type B)

(Top View)



XXX : Identification Code
Y : Year : 0~9
W : Week : A~Z : 1~26 week;
a~z : 27~52 week; z represents
52 and 53 week
X : Internal Code


| Part Number | Package | Identification Code |
|----------------------------|-----------------------|---------------------|
| AP7353-18FS4-7 | X2-DFN1010-4 (Type B) | B6A |
| AP7353-25FS4-7 | X2-DFN1010-4 (Type B) | B6B |
| AP7353-28FS4-7 | X2-DFN1010-4 (Type B) | B6C |
| AP7353-285FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B6D |
| AP7353-29FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B6E |
| AP7353-30FS4-7 | X2-DFN1010-4 (Type B) | B6F |
| AP7353-31FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B6G |
| AP7353-32FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B6H |
| AP7353-33FS4-7 | X2-DFN1010-4 (Type B) | B6J |
| AP7353-36FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B6K |
| AP7353-45FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B6L |
| AP7353D-18FS4-7 | X2-DFN1010-4 (Type B) | B7A |
| AP7353D-25FS4-7 | X2-DFN1010-4 (Type B) | B7B |
| AP7353D-28FS4-7 | X2-DFN1010-4 (Type B) | B7C |
| AP7353D-285FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B7D |
| AP7353D-29FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B7E |
| AP7353D-30FS4-7 | X2-DFN1010-4 (Type B) | B7F |
| AP7353D-31FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B7G |
| AP7353D-32FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B7H |
| AP7353D-33FS4-7 | X2-DFN1010-4 (Type B) | B7J |
| AP7353D-36FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B7K |
| AP7353D-45FS4-7 (Note 12) | X2-DFN1010-4 (Type B) | B7L |

Note: 12. This voltage is supported upon request.

Package Outline Dimensions


Please see <http://www.diodes.com/package-outlines.html> for the latest version.

(1) X1-WLB0707-4 (Type A1)



| X1-WLB0707-4 (Type A1) | | | |
|---------------------------|-------|-------|-------|
| Dim | Min | Max | Typ |
| A | 0.345 | 0.445 | 0.395 |
| A1 | 0.140 | 0.180 | 0.160 |
| A2 | 0.185 | 0.235 | 0.210 |
| A3 | 0.020 | 0.030 | 0.025 |
| b | 0.195 | 0.225 | 0.210 |
| D | 0.610 | 0.670 | 0.640 |
| E | 0.610 | 0.670 | 0.640 |
| e | -- | -- | 0.350 |
| z | -- | -- | 0.145 |
| z1 | -- | -- | 0.145 |
| All Dimensions in mm | | | |

(2) X2-DFN1010-4 (Type B)




| X2-DFN1010-4 (Type B) | | | |
|-----------------------|------|------|-------|
| Dim | Min | Max | Typ |
| A | - | 0.40 | 0.39 |
| A1 | 0.00 | 0.05 | 0.02 |
| A3 | - | - | 0.13 |
| b | 0.20 | 0.30 | 0.25 |
| D | 0.95 | 1.05 | 1.00 |
| D2 | 0.43 | 0.53 | 0.48 |
| E | 0.95 | 1.05 | 1.00 |
| E2 | 0.43 | 0.53 | 0.48 |
| e | - | - | 0.65 |
| k | 0.19 | 0.29 | 0.24 |
| L | 0.20 | 0.30 | 0.25 |
| L1 | 0.02 | 0.12 | 0.07 |
| R | 0.02 | 0.08 | 0.05 |
| z | - | - | 0.050 |
| All Dimensions in mm | | | |

Suggested Pad Layout


Please see <http://www.diodes.com/package-outlines.html> for the latest version.

(1) X1-WLB0707-4 (Type A1)



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 0.350 |
| D | 0.180 |

(2) X2-DFN1010-4 (Type B)



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 0.650 |
| X | 0.350 |
| X1 | 0.112 |
| X2 | 0.530 |
| X3 | 1.00 |
| Y | 0.350 |
| Y1 | 0.530 |
| Y2 | 1.100 |

Mechanical Data

- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals:
 - X1-WLB0707-4: Finish - tin-silver-copper (SnAgCu), Solderable per MIL-STD-202, Method 208 (e1)
 - X2-DFN1010-4 (Type B): Finish - NiPdAu over Copper Leads, Solderable per MIL-STD-202, Method 208 (e4)
- Weight:
 - X1-WLB0707-4: 0.001 grams (Approximate)
 - X2-DFN1010-4 (Type B): 0.001 grams (Approximate)

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).
2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.
3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.
4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.
5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (<https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/>) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.
7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.
8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.
9. This Notice may be periodically updated with the most recent version available at <https://www.diodes.com/about/company/terms-and-conditions/important-notice>

DIODES is a trademark of Diodes Incorporated in the United States and other countries.
The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.
© 2022 Diodes Incorporated. All Rights Reserved.

www.diodes.com