

								<u> </u>						/
	MAT'L NO.	INTERNAL THREAD	EXTERN THREA	AL D DIM.	*A*	MATERIAL / PLATING			NOTES:					
J [74962-1110	4-40 UNC-2B	4-40 UNC	-2A .338 .	/ 8.60 STAINLES	SS STEEL 303 / N	303 / NYLON TORQUE PATCH		1. PARTS ARE PACKAGED IN POLY BAGS CONSISTING OF 40 PIECES. 2. INTERNAL AND EXTERNAL THREADS TO WITHSTAND A MINIMUM APPLIED					
									TORQUE OF 3. NYLOK $^{f R}$ TO	5 lbf in/5.76 kgf RQUE PATCH LO	fcm. CATED TO THE L	_EFT OF THE FIR	ST	
									OR SECOND	FULL THREADS	AND COVERS 3 1	THREADS MINIMUM		
1														1
н														н
G									-	"A"——	-			G
							,:	SEE TABLE FOR	7	65 19				
						-		INTERNAL THREAD TYPE			SEE	E NOTE 3		
F									(<u> </u>		 MMM			F
			3		ë	216 5.49 REF.			<u> </u>					
					5	0.49								
E								<u>.187</u> 4.75			1	TABLE FOR XTERNAL		E
												EAD TYPE		
D														D
c														С
														\vdash
						3/14	QUALITY	GENERAL TOL	_ERANCES	DIMENSION STYLE	SCALE DE	SIGN UNITS O	THIRD ANGLE PROJECTION	В
В						139	SYMBOLS S T T =0	(UNLESS SPE mm 4 PLACES ±		N BY DATE	/09 TITLE TDP	3/16" HEX JA	ACKPOST	
-						3 2016-1	SSCRPTE =0	3 PLACES ± 2 PLACES ± 0,25	±.010 CHECK ± DMOR	ED BY DATE GAN 2017/07	─ WI	TH TORQUE F		
A						NOTE D: UCP:	SWILL SMILL	1 PLACE ± 0 PLACE ± ANGULA	± SMIL	RIAL NO.	/14 DOCUMENT NO.	mole	SHEET NO.	A
						MOD EC NI DRWN	APPR:SMILLER 2015/09/14 APPR:SMILLER 2015/09/17 DESCRIPTION OL ATT OL AT	DRAFT WHERE MUST RE WITHIN DIME	I\ _ '/ _	SEE TABLE THIS DRAWING CO	SD-	-74962-1110 ON THAT IS PROPR	1 OF 1	
tb a	o_frame_C_P_AM_T ev. G 2012/01/11	12	11	10	9	8 B	ହି 7	WITHIN DIME	NSIONS L	INCORPORATED AN	ND SHOULD NOT BE	USED WITHOUT W	RITTEN PERMISSION	