9001K401J1R

selector switch \emptyset 30 - 3 positions - maintained - incandescent



Main	
Range of Product	Harmony 9001K
Product or Component Type	Illuminated selector switch
Device short name	9001K
Type of operator	maintained
Operator profile	Red standard knob

Complementary

Chromium plated metal
1.18 in (30 mm)
0.54 lb(US) (0.245 kg)
Round
3 positions
Without contact block
500000 cycles
Via integral transformer
incandescent
BA 9s
110120 V AC 50/60 Hz
Basic element

Environment

Environment	
Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Electrical shock protection class	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 4 NEMA 6
Standards	UL 508 JIS C 852 JIS C 4520 EN/IEC 60947-5-1 EN/IEC 60947-5-4 CSA C22.2 No 14 EN/IEC 60947-1
Product Certifications	NEMA UL 508
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

Ordering and shipping details

21426 - 9001 K (NOT KA,KM,KX)	
CS1	
785901702009	
1	
0.54 lb(US) (0.24 kg)	
No	
MX	
	CS1 785901702009 1 0.54 lb(US) (0.24 kg) No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 18 mont	hs