Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > DDR I and DDR II Buffers > Fan-out Buffers > 93789 >

Add to myIDT [?]

You may also like.

93789DFT

DIDT.

Category: Fan-out Buffers

Generic Part: 93789 Market Group: PC CLOCK Description: PC BUFFER

Recommended Application: DDR fan out buffer for VIA P4x266/400 & PT800/880 chipsets Product Description/Features: • Max. frequency supported: 266 MHz (DDR533) • Low skew, fanout buffer • 1 to 6 differential clock distribution • l2C for functional and output control • Feedback pin for input to output synchronization • Supports up to 2 DDR

DIMMs • CMOS level control signal input



Parameters

Package	SSOP 28 (PY28)
Voltage	3.3 V
Package	SSOP 28
Speed	NA
Temperature	С
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 5.3 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temprature	240°C
Rebake Conditions	N/A
Length	10.2
Mark	R
Width	5.3
Pitch	0.65
Thickness	1.73
Status	Active