



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE6036 & NTE6037 Silicon Power Rectifier Diode 600V, 85 Amp, DO5

Features:

- Short Reverse Recovery Time
- Low Stored Charge
- Available in Cathode-to-Case (NTE6036) or Anode-to-Case (NTE6037) Style

Ratings and Characteristics:

Average Forward Current ($T_C = +75^\circ\text{C}$ Max), $I_{F(\text{AV})}$	85A
Maximum Repetitive Peak Reverse Voltage ($T_J = -40^\circ$ to $+125^\circ\text{C}$), V_{RRM}	600V
Maximum Non-Repetitive Peak Reverse Voltage ($T_J = +25^\circ$ to $+125^\circ\text{C}$, $t_p \leq 5\text{ms}$), V_{RSM}	700V
Maximum Reverse Current (At Rated V_R), I_R	
$T_J = +25^\circ\text{C}$	0.1mA
$T_J = +125^\circ\text{C}$	20mA
Maximum Forward Surge Current, I_{FSM}	
50Hz	1100A
60Hz	1151A
Fusing Current, I^2t	
50Hz	$6050\text{A}^2\text{s}$
60Hz	$5523\text{A}^2\text{s}$
Fusing Current, $I^2\sqrt{t}$	$85560\text{A}^2\sqrt{\text{s}}$
Operating Junction Temperature Range, T_J	-40° to $+125^\circ\text{C}$
Storage Temperature range, T_{stg}	-40° to $+150^\circ\text{C}$
Thermal Resistance, Junction-to-Case (DC Operation), R_{thJC}	0.30°C/W
Thermal Resistance, Case-to-Sink (Surface flat, smooth, and greased), R_{thCS}	0.25°C/W
Maximum Mounting Torque (Non-lubricated threads), T	22 (2.5) in•lb (m•N)

Electrical Specifications:

Parameter	Symbol	Test Conditions		Rating	Unit		
Maximum Average Forward Current	I_F (AV)	180° sinusoidal condition, $T_C = +75^\circ\text{C}$ Max		85	A		
Maximum Peak One-Cycle Non-Repetitive Surge Current	I_{FSM}	$t = 10\text{ms}$	Half sinewave current, rated V_{RRM} reapplied, initial $T_J = +125^\circ\text{C}$		1100 A		
		$t = 8.3\text{ms}$	1151	A			
		$t = 10\text{ms}$	Half sinewave current, no voltage reapplied, initial $T_J = +125^\circ\text{C}$		1308 A		
		$t = 8.3\text{ms}$			1369 A		
Maximum I^2t for Fusing	I^2t	$t = 10\text{ms}$	Rated V_{RRM} reapplied, initial $T_J = +125^\circ\text{C}$		6050 A^2s		
		$t = 8.3\text{ms}$			5523 A^2s		
Maximum I^2t for Individual Device Fusing		$t = 10\text{ms}$	No voltage reapplied, initial $T_J = +125^\circ\text{C}$		8556 A^2s		
		$t = 8.3\text{ms}$			7810 A^2s		
Maximum $I^2\sqrt{t}$	$I^2\sqrt{t}$	$t = 0.1$ to 10ms , no voltage reapplied, Note 1			85560 $\text{A}^2\sqrt{\text{t}}$		
Maximum Peak Forward Voltage	V_{FM}	$T_J = +25^\circ\text{C}$, $I_{FM} = 267\text{A}$			1.75 V		
Maximum Reverse Recovery Time	t_{rr}	$T_J = +25^\circ\text{C}$, $I_F = 1\text{A}$ to $V_R = 30\text{V}$, $-dI_F/dt = 100\text{A}/\mu\text{s}$			120 ns		
		$T_J = +25^\circ\text{C}$, $I_F = 267\text{A}$, $-dI_F/dt = 25\text{A}/\mu\text{s}$			500 ns		
Maximum Reverse Recovery Charge	Q_{RR}	$T_J = +25^\circ\text{C}$, $I_F = 1\text{A}$ to $V_R = 30\text{V}$, $-dI_F/dt = 100\text{A}/\mu\text{s}$			340 nC		
		$T_J = +25^\circ\text{C}$, $I_F = 267\text{A}$, $-dI_F/dt = 25\text{A}/\mu\text{s}$			1300 nC		

Note 1. I^2t for time $t_x = I^2\sqrt{t} \bullet \sqrt{t_x}$.

