

VSC3340-31

3.5 Gbps 40 × 40 Crosspoint Switch

Microsemi’s multichannel 3.5 Gbps crosspoint switch provides a cost-effective solution for high-speed copper interconnects.

The VSC3340-31 is an advanced signal conditioning crosspoint switch solution uniquely capable of addressing a wide array of asynchronous, physical layer switching, and routing applications across storage, server, video, communications, and other industries. Featuring a 40 × 40 non-blocking, multicasting switch core with ports running at any rate up to 3.5 Gbps, the VSC3340-31 architecture provides protocol-transparent operation, allowing each channel to run independently. VSC3340-31 supports virtually all standard and proprietary data protocols up to the maximum data rate.

The device incorporates Microsemi’s fourth-generation input equalization and pre-emphasis I/O capability engineered to overcome channel impairments experienced in today’s high-density systems at multi-gigabit data rates. It can perform signal fanout, loopback, and protection switching. It can also regenerate signals compromised by losses in the transmission medium. Microsemi’s equalization provides highly effective compensation for deterministic jitter across a wide range of high-speed interconnect applications.


Highlights

- DC to 3.5 Gbps operation
- 40 × 40 fully non-blocking switch capability
- Protocol-independent operation
- Advanced input equalization and output pre-emphasis
- Small 23 mm × 23 mm form factor

Applications

- Servers
- Storage
- HDMI/DVI/DisplayPort switching/routing
- Broadcast video switching/routing

VSC3340-31 Line Card and Central Switch Card Applications



Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

VSC3340-31

3.5 Gbps 40 × 40 Crosspoint Switch

Speed and Protocol Support

- 3.5 Gbps non-return-to-zero (NRZ) data bandwidth
- Protocol-independent asynchronous operation

Architecture

- Fully non-blocking and multicasting switch core
- Loss of signal (LOS) detection and forwarding (supports out-of-band signaling)
- Fully asynchronous operation with <1 ns latency
- 40 × 40 switch core enables signal fanout, loopback, and protection switching

Signal Integrity

- Multiple time-constant programmable input and output equalization
- Wide equalization adjustment range
- Input EQ
- Output pre-emphasis

Key Specifications

- 3.5 Gbps NRZ per channel data rate
- 2.5 V power supply
- 23 mm × 23 mm flip chip ball grid array package

Related Products

Visit www.microsemi.com for information about these related products:

- Crosspoint switches
- Ethernet MACs
- Mux, demux, and transceivers
- Electronic dispersion compensation CDRs

