Product data sheet Characteristics

XGFEC2525

Radio frequency identification XG, field expander universal type, Sn 26...150 mm, 250 x 250 x 10 mm



Main	
Range of Product	Telemecanique Radio frequency identification XG
Accessory / Separate Part Type	Field expander
Product Specific Application	Universal
Product Compatibility	XGCS4901201 + XGHB440245 XGCS4901201 + XGHB90E340 XGCS4901201 + XGHB320246 XGCS4901201 + XGHB221346 XGCS4901201 + XGHB320345 XGCS4901201 + XGHB520246
Accessory / separate part destination	Station with associated label
[Sn] nominal sensing distance	1.025.91 in (26150 mm)

Complementary

Accessory dimension	250 x 250 x 10 mm

Ordering and shipping details

Category	22491-SENS,IDENTIFICATION DEVICE (XGK)	
Discount Schedule	DS2	
GTIN	3606480074899	
Nbr. of units in pkg.	1	
Package weight(Lbs)	18.24 oz (517.0 g)	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	3.54 in (9 cm)	
Package 1 width	11.69 in (29.7 cm)	
Package 1 Length	11.81 in (30 cm)	
Unit Type of Package 2	S04	
Number of Units in Package 2	6	
Package 2 Weight	8.76 lb(US) (3.974 kg)	
Package 2 Height	11.81 in (30 cm)	
Package 2 width	15.75 in (40 cm)	
Package 2 Length	23.62 in (60 cm)	
Package 3 Height	28.94 in (73.5 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	[™] REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	


Contractual warranty

Warranty	18 months

XGFEC2525

Dimensions

Field Expanders




(1) 4 x M4 screws

XGFEC2525

Minimum Mounting Distances


Distance Between Field Expanders



Tag	e1	e2	e3
XGHB90E340 XGHB520246	570	890	960
XGHB320345	720	1275	1200

Minimum Mounting Distances in a Metal Structure

Distance Between Field Expanders




Field expanders	
e (mm)	h (mm)
0	75

XGFEC2525

Curves


Dialogue Zones for Field Expanders



(1) Recommended working zone.

Curves

Dialogue Zones for Field Expanders



(1) Recommended working zone.