

PM300CL1A060

FLAT-BASE TYPE INSULATED PACKAGE

PM300CL1A060



FEATURE

Inverter + Drive & Protection IC


- a) Adopting new 5th generation Full-Gate CSTBT™ chip
 - b) The over-temperature protection which detects the chip surface temperature of CSTBT™ is adopted.
 - c) Error output signal is possible from all each protection upper and lower arm of IPM.
 - d) Compatible L-series package.
 - 3Ø 300A, 600V Current-sense and temperature sense IGBT type inverter
 - Monolithic gate drive & protection logic
 - Detection, protection & status indication circuits for, short-circuit, over-temperature & under-voltage (P-Fo available from upper arm devices)
 - UL Recognized

APPLICATION

General purpose inverter, servo drives and other motor controls


PACKAGE OUTLINES

Dimensions in mm



November 2012

INTERNAL FUNCTIONS BLOCK DIAGRAM

MAXIMUM RATINGS ($T_j = 25^\circ\text{C}$, unless otherwise noted)

INVERTER PART

Symbol	Parameter	Condition	Ratings	Unit
V _{CES}	Collector-Emitter Voltage	$V_D = 15\text{V}$, $V_{CIN} = 15\text{V}$	600	V
$\pm I_C$	Collector Current	$T_c = 25^\circ\text{C}$	(Note-1) 300	A
$\pm I_{CP}$	Collector Current (Peak)	$T_c = 25^\circ\text{C}$	600	A
P _c	Collector Dissipation	$T_c = 25^\circ\text{C}$	(Note-1) 833	W
T _j	Junction Temperature		-20 ~ +150	°C

*: Tc measurement point is just under the chip.

CONTROL PART


Symbol	Parameter	Condition	Ratings	Unit
V _D	Supply Voltage	Applied between : $V_{UP1}-V_{UPC}$, $V_{VP1}-V_{VPC}$, $V_{WP1}-V_{WPC}$, $V_{N1}-V_{NC}$	20	V
V _{CIN}	Input Voltage	Applied between : U_P-V_{UPC} , V_P-V_{VPC} , W_P-V_{WPC} , $U_N \bullet V_N \bullet W_N-V_{NC}$	20	V
V _{FO}	Fault Output Supply Voltage	Applied between : $UFO-V_{UPC}$, $VFO-V_{VPC}$, $WFo-V_{WPC}$, $FO-V_{NC}$	20	V
I _{FO}	Fault Output Current	Sink current at UFO , VFO , WFo , FO terminals	20	mA

TOTAL SYSTEM

Symbol	Parameter	Conditions	Ratings	Unit
$V_{CC(prot)}$	Supply Voltage Protected by SC	$V_D = 13.5V \sim 16.5V$ Inverter Part, $T_j = +125^\circ C$ Start	400	V
$V_{CC(surge)}$	Supply Voltage (Surge)	Applied between : P-N, Surge value	500	V
T_{stg}	Storage Temperature		-40 ~ +125	°C
V_{iso}	Isolation Voltage	60Hz, Sinusoidal, Charged part to Base plate, AC 1min, RMS	2500	V

*: T_C measurement point is just under the chip.**THERMAL RESISTANCE**

Symbol	Parameter	Conditions	Limits			Unit
			Min.	Typ.	Max.	
$R_{th(j-c)Q}$	Thermal Resistance	Inverter, IGBT (per 1 element)	(Note.1)	-	-	0.15
$R_{th(j-c)F}$		Inverter, FWDi (per 1 element)	(Note.1)	-	-	0.23
$R_{th(c-f)}$	Contact Thermal Resistance	Case to fin, (per 1 module) Thermal grease applied	(Note.1)	-	-	0.023

Note.1: If you use this value, $R_{th(f-a)}$ should be measured just under the chips.

* "350G" is printed on the label

ELECTRICAL CHARACTERISTICS ($T_j = 25^\circ C$, unless otherwise noted)**INVERTER PART**

Symbol	Parameter	Conditions	Limits			Unit
			Min.	Typ.	Max.	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$V_D=15V$, $I_c=300A$	$T_j=25^\circ C$	-	1.75	2.35
		$V_{CIN}=0V$, Pulsed		-	1.75	2.35
V_{EC}	FwdDi Forward Voltage	$-I_c=300A$, $V_D=15V$, $V_{CIN}=15V$	(Fig. 2)	-	1.7	2.8
t_{on}	Switching Time	$V_D=15V$, $V_{CIN}=0V \rightarrow 15V$ $V_{CC}=300V$, $I_c=300A$ $T_j=125^\circ C$ Inductive Load	(Fig. 3,4)	0.3	0.8	2.0
t_{rr}				-	0.4	0.8
$t_{c(on)}$				-	0.4	1.0
t_{off}				-	1.0	2.3
$t_{c(off)}$				-	0.3	1.0
I_{CES}	Collector-Emitter Cut-off Current	$V_{CE}=V_{CES}$, $V_D=15V$, $V_{CIN}=15V$ (Fig. 5)	$T_j=25^\circ C$	-	-	1
			$T_j=125^\circ C$	-	-	10

CONTROL PART

Symbol	Parameter	Condition	Limits			Unit	
			Min.	Typ.	Max.		
Id	Circuit Current	Vd = 15V, Vcin = 15V	Vn1-Vnc	—	6	12	mA
			V*p1-V*pc	—	2	4	
Vth(ON)	Input ON Threshold Voltage	Applied between : UP-VUPC, VP-VVPC, WP-VWPC UN • VN • WN-VNC	1.2	1.5	1.8	V	
			1.7	2.0	2.3		
SC	Short Circuit Trip Level	—20 ≤ Tj ≤ 125°C, Vd = 15V (Fig. 3,6)	600	—	—	A	
toff(SC)	Short Circuit Current Delay Time	Vd = 15V (Fig. 3,6)	—	0.2	—	μs	
OT	Over Temperature Protection	Detect Temperature of IGBT chip	Trip level	135	—	—	°C
			Hysteresis	—	20	—	
UV	Supply Circuit Under-Voltage Protection	—20 ≤ Tj ≤ 125°C	Trip level	11.5	12.0	12.5	V
			Reset level	—	12.5	—	
IFO(H)	Fault Output Current	Vd = 15V, Vcin = 15V (Note-2)	—	—	0.01	mA	
			—	10	15		
tFO	Minimum Fault Output Pulse Width	Vd = 15V (Note-2)	1.0	1.8	—	ms	

(Note-2) Fault output is given only when the internal SC, OT & UV protections schemes of either upper or lower arm device operate to protect it.


MECHANICAL RATINGS AND CHARACTERISTICS

Symbol	Parameter	Condition	Limits			Unit	
			Min.	Typ.	Max.		
—	Mounting torque	Mounting part	screw : M5	2.5	3.0	3.5	N • m
		Main terminal part	screw : M5	2.5	3.0	3.5	
—	Weight	—		—	800	—	g

RECOMMENDED CONDITIONS FOR USE



Symbol	Parameter	Condition	Recommended value	Unit
Vcc	Supply Voltage	Applied across P-N terminals	≤ 400	V
Vd	Control Supply Voltage	Applied between : VUP1-VUPC, VVP1-VVPC VWP1-VWPC, VN1-VNC (Note-3)	15.0 ± 1.5	V
VCIN(ON)	Input ON Voltage	Applied between : UP-VUPC, VP-VVPC, WP-VWPC UN • VN • WN-VNC	≤ 0.8	V
	Input OFF Voltage		≥ 9.0	
fPWM	PWM Input Frequency	Using Application Circuit of Fig. 8	≤ 20	kHz
tdead	Arm Shoot-through Blocking Time	For IPM's each input signals (Fig. 7)	≥ 2.0	μs

(Note-3) With ripple satisfying the following conditions: dv/dt swing ≤ ±5V/μs, Variation ≤ 2V peak to peak




PRECAUTIONS FOR TESTING

- Before applying any control supply voltage (V_D), the input terminals should be pulled up by resistors, etc. to their corresponding supply voltage and each input signal should be kept off state.
After this, the specified ON and OFF level setting for each input signal should be done.
- When performing "SC" tests, the turn-off surge voltage spike at the corresponding protection operation should not be allowed to rise above V_{CES} rating of the device.
(These test should not be done by using a curve tracer or its equivalent.)



a) Lower Arm Switching



b) Upper Arm Switching




Fig. 3 Switching time and SC test circuit




Fig. 4 Switching time test waveform





Fig. 6 SC test waveform


1.5V: Input on threshold voltage $V_{th(on)}$ typical value, 2V: Input off threshold voltage $V_{th(off)}$ typical value

Fig. 7 Dead time measurement point example




Fig. 8 Application Example Circuit

NOTES FOR STABLE AND SAFE OPERATION ;

- Design the PCB pattern to minimize wiring length between opto-coupler and IPM's input terminal, and also to minimize the stray capacity between the input and output wirings of opto-coupler.
- Connect low impedance capacitor between the Vcc and GND terminal of each fast switching opto-coupler.
- Fast switching opto-couplers: $t_{PLH}, t_{PHL} \leq 0.8\mu s$, Use High CMR type.
- Slow switching opto-coupler: $CTR > 100\%$
- Use 4 isolated control power supplies (VD). Also, care should be taken to minimize the instantaneous voltage change of the power supply.
- Make inductance of DC bus line as small as possible, and minimize surge voltage using snubber capacitor between P and N terminal.
- Use line noise filter capacitor (ex. $4.7nF$) between each input AC line and ground to reject common-mode noise from AC line and improve noise immunity of the system.

November 2012

PERFORMANCE CURVES

