


## RS1AL THRU RS1ML SINGLE PHASE 1.0AMP SURFACE MOUNT FAST RECOVERY RECTIFIER



### Features

- Glass passivated device
- Ideal for surface mounted applications
- Low reverse leakage
- Metallurgically bonded construction
- High temperature soldering guaranteed: 260 C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension
- Plastic material-UL flammability 94V-0
- This is a Halogen Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

### Circuit Diagram



### Mechanical Data

- Case: SOD-123FL, molded plastic
- Terminals: Plated leads, solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any

### Maximum Ratings and Electrical Characteristics @T<sub>A</sub>=25°C unless otherwise specified

Type Number	Symbol	RS1 AL	RS1 BL	RS1 DL	RS1 GL	RS1 JL	RS1 KL	RS1 ML	Units
Marking Code		R1AL	R1BL	R1DL	R1GL	R1JL	R1KL	R1ML	
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V <sub>R(RMS)</sub>	35	70	140	280	420	560	700	
Average Rectified Output Current @T <sub>A</sub> = 30°C	I <sub>O</sub>	1.0							A
Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	30.0							A
Forward Voltage @I <sub>F</sub> = 1.0A, T <sub>J</sub> =25°C	V <sub>F</sub>	1.3							V
Maximum DC reverse current at rated DC blocking voltage	I <sub>R</sub>	5.0 100							μA
Typical junction capacitance (Note 1)	C <sub>J</sub>	15							pF
Maximum Reverse Recovery Time (Note 2)	T <sub>rr</sub>	150				250	500		ns
Typical thermal resistance (Note 3)	R <sub>θJA</sub>	85							°C/W
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150							°C

**Note:** 1. Measured at 1.0 MHz and applied reverse voltage of 4.0 VDC  
 2. Measured with I<sub>F</sub>=0.5A, I<sub>R</sub>=1.0A, I<sub>rr</sub>=0.25A,  
 3. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. Mounted

**Ratings and Characteristics Curves**

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS






Fig.5 TYPICAL CAPACITANCE



**Mechanical Dimensions SOD-123FL(Inches/Millimeters)**



**Ordering Information**

Device	Package	Shipping
RS1AL THRU RS1ML	SOD-123FL	3000pcs / reel
RS1ALTR THRU RS1MLTR	SOD-123FL	3000pcs / reel


For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

**Marking Diagram**



R1AL = Marking Code

**Carrier Tape Specification SOD-123FL**



SYMBOL	Millimeters	
	Min.	Max.
A	1.95	2.15
B	3.85	4.05
C	1.35	1.55
d	1.50	1.60
E	1.65	1.85
F	3.40	3.60
P	3.90	4.10
P0	3.90	4.10
P1	1.90	2.10
W	7.90	8.30



**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..