UNCONTROLLED DOCUMENT

PART NUMBER
SSF-LXH303GD

REV. Ε

REV.	E.C.N. NUMBER AND REVISION COMMENTS	D/	4TE
Α	REDRAWN.	12.	6.93
В	CHANGED DIMS.	12.1	16.93
С	UPDATED OPER. SPECS.	10.1	12.94
D	E.C.N. #10BRDR. & REDRAWN.	9.2	2.98
E	E.C.N. #10BRDR.	4.	6.01

4.03 [0.159]	2.50 [0.098] - 5.26 [0.207]
ø2.90 [ø0.114] + 6.33 [0.249]	2
3.17 [0.125]	1)
ANDDE	3.18 [0.125]
2.54 [0.100] - 0.50 [0.020 SQR. (2 PL	

ELECTRO-OPTICAL CHA	ARACTERI	STICS TA=25°C	;	I _f =20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		565 (GREEN)		nm	
FORWARD VOLTAGE		2.2	2.6	٧f	
REVERSE VOLTAGE	5.0			v_r	Ir=100µA
AXIAL INTENSITY		30		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		60		2x theta	
EMITTED COLOR:	GREEN				
EPOXY LENS FINISH:	GREEN	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C

MAX	UNITS
150	mA
25	mA
105	mW
- 1.6	m W/° C
- 40 TO +85	. C
+ 260	. C
	3 SEC. MAX
	150 25 105 - 1.6 - 40 TO +85

^{*} t<10µS

NOTES:

- 1. SSL-LX3044GD, GREEN LED.
- 2. SSH-LXH303 HOLDER, BLACK NYLON, UL 94V-0.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECIS

REV.

PART NUMBER SSF-LXH303GD

T-3 (T-1) LED FAULT INDICATOR, 565nm GREEN LED, GREEN DIFFUSED LENS. CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

<u>RELIABILITY NOTE</u>

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CT

CHECKED BY: APPROVED BY: DATE: 9.11.91

PAGE: 1 OF 1 SCALE: N/A

E D